

APPENDIX OF PENDING CLAIMS

1. A generator for converting mechanical energy to electrical energy, the generator comprising:
 - at least two electrodes; and
 - a polymer arranged in a manner which causes a change in electric field in response to a deflection applied to a first portion of the polymer, wherein a second portion of the polymer is elastically pre-strained.
2. The generator of claim 1 wherein the generator is stretched before the deflection.
3. The generator of claim 2 wherein the at least two electrodes apply a voltage that produces a pressure in the polymer less than elastic restoring stresses resulting from the stretch.
4. The generator of claim 2 wherein the deflection is a contraction in one direction.
5. The generator of claim 4 wherein electrical energy is removed by the at least two electrodes during the contraction.
6. The generator of claim 1 wherein the polymer has an elastic modulus below about 100 MPa.
7. The generator of claim 1 further comprising a mechanical input that provides the deflection and mechanical energy.
8. The generator of claim 1 wherein the polymer has a substantially constant thickness and the deflection comprises a decrease in net area of the polymer orthogonal to the thickness.
9. The generator of claim 1 wherein the polymer has a maximum linear strain of at least about 50 percent.
10. The generator of claim 9 wherein the polymer has a maximum linear strain of at least about 100 percent.
11. The generator of claim 1 wherein the polymer has a maximum area strain of at least about 100 percent.
12. The generator of claim 1 wherein the pre-strain is applied to a first orthogonal direction at a pre-strain greater than pre-strain in a second orthogonal direction.
13. The generator of claim 12 wherein the pre-strain applied to the first orthogonal direction is used to enhance the change in electric field from a deflection in the second orthogonal direction.
14. The generator of claim 12 wherein the polymer is pre-strained by a factor in the range of about 1.5 times to 50 times an original area prior to pre-strain.
15. The generator of claim 1 further comprising an electric circuit electrically coupled to the at least two electrodes.

16. The generator of claim 1 wherein the polymer comprises a material selected from the group consisting of silicone elastomer, acrylic elastomer, polyurethane copolymer comprising PVDF, and combinations thereof.

17. The generator of claim 1 wherein the polymer can support a change in electric field at most about 440 MegaVolts/meter.

18. The generator of claim 1 wherein electrical energy generated by deflection of the polymer generates at least about 0.15 Joules per gram for the polymer.

19. The generator of claim 1 wherein the generator is used in a heel strike generator.

20. The generator of claim 1 wherein one of the at least two electrodes is compliant.

21. A generator for converting mechanical energy to electrical energy, the generator comprising:

at least two electrodes; and

a polymer having a substantially constant thickness and an area orthogonal to the thickness, the polymer arranged in a manner which causes a change in electric field in response to a net area decrease of the polymer for the area orthogonal to the thickness.

22. The generator of claim 21 wherein the generator is stretched before the change in electric field.

23. The generator of claim 22 wherein the at least two electrodes apply a voltage that produces a pressure in the polymer less than the elastic restoring forces resulting from the stretch.

24. A generator for converting from electrical energy to mechanical energy, the generator comprising:

at least one transducer, each transducer comprising:

at least two electrodes, and

a polymer arranged in a manner which causes a change in electric field in response to a deflection applied to a first portion of the polymer; and

a frame attached to a second portion of the polymer, the frame comprising at least one aperture, wherein the first portion of the polymer is arranged in a manner which causes a change in electric field in response to a deflection applied to a third portion of the polymer.

25. The generator of claim 24 wherein the transducer is stretched before deflection of the third portion of the polymer.

26. The generator of claim 25 wherein the at least two electrodes apply a voltage that produces a pressure in the polymer less than elastic restoring stresses resulting from the stretch.

27. The generator of claim 26 further including a bias pressure.
28. A generator for converting mechanical energy in a first direction into electrical energy, the generator comprising:
- at least one transducer, each transducer comprising:
 - at least two electrodes, and
 - a polymer arranged in a manner which causes a change in electric field in response to a deflection in the first direction; and
 - a flexible frame coupled to the polymer, the frame providing improved conversion from mechanical to electrical energy for the at least one transducer.
29. The generator of claim 28 wherein the transducer is stretched before the change in electric field.
30. The generator of claim 28 wherein the at least two electrodes apply a voltage that produces a pressure in the polymer less than the elastic restoring stresses resulting from the stretch.
31. The generator of claim 28 wherein the polymer comprises pre-strain.
32. The generator of claim 31 wherein the polymer comprises pre-strain in a second direction which improves energy conversion in the first direction.
33. A generator for converting mechanical energy in a first direction into electrical energy, the generator comprising:
- at least one transducer, each transducer comprising:
 - at least two electrodes, and
 - a polymer arranged in a manner which causes a change in electric field in response to a deflection in the first direction; and
 - at least one stiff member coupled to the at least one transducer, the at least one stiff member substantially preventing displacement in a second direction.
34. The generator of claim 33 wherein the polymer has a compliance in one direction greater than in a second.
35. The generator of claim 33 wherein the polymer has an aspect ratio of at least 4:1.
36. The generator of claim 33 wherein the at least one stiff member is coupled to an edge of the polymer.

**BEFORE THE OFFICE OF ENROLLMENT AND DISCIPLINE
UNITED STATES PATENT AND TRADEMARK OFFICE**

LIMITED RECOGNITION UNDER 37 CFR § 10.9(b)

William Plut is hereby given limited recognition under 37 CFR § 10.9(b) as an employee of the Beyer, Weaver, and Thomas, LLP law firm to prepare and prosecute patent applications wherein the patent applicant is the client of the Beyer, Weaver, and Thomas, LLP law firm, and the attorney or agent of record in the applications is a registered practitioner who is a member of the Beyer, Weaver, and Thomas, LLP law firm. This limited recognition shall expire on the date appearing below, or when whichever of the following events first occurs prior to the date appearing below: (i) William Plut ceases to lawfully reside in the United States, (ii) William Plut's employment with the Beyer, Weaver, and Thomas, LLP law firm ceases or is terminated, or (iii) William Plut ceases to remain or reside in the United States on an TN visa.

This document constitutes proof of such recognition. The original of this document is on file in the Office of Enrollment and Discipline of the United States Patent and Trademark Office.

Expires: June 10, 2002



William J. Griffin, Acting Director
Office of Enrollment and Discipline